



AUSTRALIAN MESH

PTY LTD
ACN 613 929 285
ABN 19 613 929 285

VICTORIA

1/3 BUNGALEEN CRT DANDENONG
PHONE: 03 9794 5353 FAX: 03 9706 4353

QUEENSLAND

17 HOVEY ROAD YATALA
PHONE: 07 3382 7169 FAX: 07 3807 5611

EMAIL: sue@australianmesh.com.au

WEB: www.australianmesh.com.au

DATA SHEET FOR MESH STRIP

Specifications

Material: 2mm galvanized bend strip – folded to 30mm on each side of fold
Length: 1950mm
Pre punched: 1st fold – 13 holes – hole size approx 10mm (for attaching screws)
2nd fold – 13 holes – hole size approx 5mm (for attaching line wire)

Holes are pre punched: 1 at each end of the strip – 75mm from edge
Holes are pre punched: 11 at 150mm apart

Weight: Each strip weighs 1.8kg

Testing: Strips are tested to conform to Standard AS/NZS 4389:2015
Tested Using: Hex Head Tex Screws (10 x 16) and
Tested Using: Wafer Head Screws (10 x 16)

Installation: Attach either Hex Head Tex Screws or Wafer Head Screws as above to
The top part of the strip (with the larger holes)

Attach screw to first and last hole, then every 300mm
(in total 7 SCREWS)

For Timber purlins please use 50mm batten screws

All longitudinal wires to be passed through the anchor point with a
Minimum of 4 full turns. (see attached photo)



MESH STRIP INSTALLATION USING HEX HEAD TEX SCREWS (12 X 25)

*You can't put a foot wrong with Australian Owned & Manufactured Ausmesh 300 Safety Mesh
Prepared by Sue Dobson 17/03/2017*