

AUSTRALIAN MESH

A DIVISION OF SKILLTRACK PTY LTD
ABN NO 66 970 065 755

EMAIL: info@australianmesh.com.au

Queensland

17-19 HOVEY ROAD, YATALA QLD 4207
PH: 07 3382 7169
FAX: 07 3807 5611

Melbourne

1/3 BUNGALEEN CRT DANDENONG VIC 3175
PH: 03 9794 5353
FAX: 03 9706 4353

Australian Mesh is the original manufacturer of Safety Roof Mesh known as “Ausmesh 300”. It is designed to support insulation and to help prevent construction roof workers from falling.

Safety is Everyone’s Business

Everyone involved in the construction industry has an obligation to ensure building and maintenance activities are carried out as safely as possible. It begins at design stage with architects and specifiers, right through to builders and sub contractors.

Ausmesh 300 Safety Mesh

Australian Mesh recommends the use of **Ausmesh 300** to assist in the prevention of falls during sheet laying. **Ausmesh 300** offers long term protection for workers when securely fixed to the structure over the area to be roofed and used in conjunction with appropriate edge and perimeter protection.

Ausmesh 300 Safety Mesh meets all the requirements of the following:

- Australian Standard AS/NZS4389
- Code of Practices throughout Australia

CAN BE USED IN:

Factories, Warehouses, Shopping Centres, Schools, Office Blocks, Sheds

FEATURES:

Strong secure joins – Meets Australian Standard AS/NZS4389 – Test Certificate Available on request – Australian made Product

BENEFITS:

High level of workers security – retains insulation materials – easy to install – corrosion resistant

SPECIFICATIONS:

- **Width:** 1800mm, 2250mm or 2400mm
- **Diameter:** 2mm wire
- **Mesh:** 300mm x 150m
- **Length:** 50 metres
- **Coating:** Galvanised

AUSTRALIAN MESH

A DIVISION OF SKILLTRACK PTY LTD
ABN NO 66 970 065 755

EMAIL: info@australianmesh.com.au

Queensland

17-19 HOVEY ROAD, YATALA QLD 4207
PH: 07 3382 7169
FAX: 07 3807 5611


Melbourne


1/3 BUNGALEEN CRT DANDENONG VIC 3175
PH: 03 9794 5353
FAX: 03 9706 4353


AUSMESH 300 SAFETY MESH

Recommended Fixing Details


ANCHOR POINTS - Pass all longitudinal wires around, or through anchor points, twisting the tail of each wire four times around the main portion of the same wire (see below).

A)  Wrap longitudinal wires around steel or wood purlin.


B)  Pass longitudinal wires through holes drilled in purlins.

C)  Pass longitudinal wires through 40mm long by 3.15mm diameter staples.

SIDE OVERLAPS - Overlap sides by 150mm (see right). If purlin space is greater than 1700mm, the overlap is to be tied between purlins.



JOINING ROLLS/SECTIONS - Place the two transverse wires together twisting the longitudinal tail wires (approx. 300mm long) around each other. Then twist one longitudinal wire FOUR times around the main portion of the same wire. Twist the other longitudinal wire ONCE around the main portion of the same wire and then FOUR times around the two transverse wires (see right).



This publication has been prepared by Australian Mesh (A Division of Skilltrack Pty Ltd) ABN No 66 970 065 755. Please note that the specifications and technical data are subject to change without notice and to ensure accuracy users of this publication are requested to check the information to satisfy themselves and not to rely on the information without first doing so. Unless required by law the company cannot accept any responsibility for any loss, damage or consequence resulting from the use of this publication. This brochure is not an offer to trade and shall not form any part of the trading terms in any transaction.

Copyright 2004 Australian Mesh ABN 66970065755 – Registered Trademark Ausmesh 300.